

### FLOORTEX® FLOOR COATING

# one day professional high quality installation

#### A Total Transformation

Garage Living specializes in the preparation of concrete surfaces and the application of the highest quality concrete floor coatings available on the market. Using polyaspartic coatings, our professionally trained applicators will transform your garage floor in as little as one day. The Floortex® coating system and professional application transforms a dirty, dusty and damaged concrete floor into a clean, durable and attractive surface that fits with the rest of your home and lifestyle.

#### HARBOR BLUE FLOOR & GL CUSTOM CABINETRY



# NIGHTFALL FLOOR



#### **FEATURES & BENEFITS**

**FAST CURE** Rapid turnaround time\* under normal conditions for foot and vehicle traffic. \*\*

LOW ODOR Lower odor than most polyaspartics.

LOW TEMPERATURE CURE Will cure in temperatures as low as -40°F (-40°C).

**FOOD CONTACT SAFETY** Meets USDA/CFSAN, U.S. Food Code, physical facilities criteria.

**HIGH FLEXIBILITY** Passes 90° Mandrel bend test.

 $\ensuremath{\mathbf{UV}}$   $\ensuremath{\mathbf{RESISTANT}}$  Excellent UV resistance, non-yellowing and high gloss characteristics.

**LOW VOC** Ultra low VOC and also in zero VOC formulation for restricted areas where adequate ventilation does not exist.

#### \*In Warmer Temperatures (April to October):

Return to light foot traffic in 12 hours and wait 24 hours for everyday use. Return garage contents to their new organized space in 48 hours. Return to vehicle traffic in 96 hours.

**IMPACT & ABRASION RESISTANT** Excellent abrasion and impact resistance.

CHEMICAL RESISTANT Excellent chemical resistance.

HOT TIRE PEEL RESISTANT Resistant to hot tire peel.

**HIGH TEMPERATURE RESISTANT** Tolerant to 300°F (149°C) for random, incidental heat contact.

**COLOR PALETTE** Multiple flooring color options to match your garage decor

**EXCELLENT ADHESION & BONDING** Bonds to virtually all substrates of any dimension, including metals, concrete, fiberglass and wood.

**HIGH ELONGATION** Will stretch 100% of its own dimension to prevent crack re-appearance.

#### \*\*In Colder Temperatures (November to March):


Return to light foot traffic in 12 - 36 hours and wait 24 - 48 hours for everyday use. Return garage contents to their new organized space in 48 - 72 hours. Return to vehicle traffic in 96 - 120 hours.

Weather and environmental conditions may cause curing times to vary. Please consult your Garage Living Professional.



### FLOORTEX® FLOOR COATING

#### **STANDARD COLORS\***



































#### **PROCESS**


STEP 5 | CLEAR DURABLE FLOORTEX® TOP COAT

STEP 4 | DECORATIVE FLOORTEX® FLAKES

STEP 2 | CRACK & CHIP REPAIR

#### **PRIMARY APPLICATIONS**

Floortex® creates a durable, seamless lining which conforms to any shape and size. Excellent durability and enhanced aesthetics for floors, verticals, and other surfaces, including: Garage Floors, Exterior Patios, Pool Decks, Laboratories, Industrial Shop Floors Restaurant Floors, Airplane Hangars, Lobby Areas, Maintenance Facilities.



CHEMICAL RESISTANCE:	
Chemicals	Result
Acetic Acid 100%	С
Acetone	С
Ammonium Hydroxide 50%	RC
Anti-freeze	R
Benzene	С
Brake Fluid	R
Brine saturated H2O	R
Chlorinated H2O	R
Clorox(10%) H2O	R
Diesel fuel	RC
Dissolved Rock Salt	R
Gasoline	RC
Gasoline/5% MTBE	RC
Gasoline/5% Methanol	RC

Chemicals	Result
Hydrochloric Acid 20%	R
Hydrofluoric Acid 10%	NR
Hydraulic fluid (oil)	RC
Isopropyl Alcohol	RC
Lactic Acid	RC
MEK	RC
Methanol	R
Methylene Chloride	С
Mineral Spirits	RC
Motor Oil	R
MTBE	С
Muriatic Acid 10%	R
NaCI/H2O 10%	R
Nitric Acid 20%	NR

Chemicals	Result
Phosphoric Acid 10%	R
Phosphoric Acid 50%	NR
Potassium Hydroxide 10%	R
Potassium Hydroxide 20%	R Dis
Propylene Carbonate	RC
Skydrol	С
Sodium Hydroxide 25%	R
Sodium Hydroxide 50%	R Dis
Sodium Hypchlorite 10%	R
Sodium Bicarbonate	R
Stearic Acid	R
Sugar/H20	R
Sulfuric Acid 10%	R

Chemicals	Result
Sulfuric Acid >50%	RC
Toluene	R
Transmission Fluid	R
1, 1,1-Trichlorethane	С
Trisodium Phosphate	R
Vinegar/H2O 5%	R
Xylene	RC

#### **Chemical Resistance: Chart Key**

R recommended/little or no visible damage

RC recommended conditional/some effect, swelling or discoloration

C Conditional/Cracking-wash within one hour of spillage to avoid affects

**NR** Not recommended Dis discolorative

GARAGE LIVING | 201 Chrislea Rd, Vaughan, ON L4L 8N6 | garageliving.com | 905-856-7175 PART# 10FLRTXISO / PART# 10FLRTXRSN




## FLOORTEX® STONE SERIES

# EXQUISITE TIMELESS INNOVATIVE

#### Introducing the Floortex® Stone Series.

Where luxury meets innovation in six new colors. This timeless collection is inspired by the elegance of natural stone, offering both durability and sophistication. Our refined textures, featuring flakes finer than ever before, elevate any garage space with a touch of luxury. Whether you're seeking timeless elegance or exceptional quality, the FLOORTEX® Stone Series is designed for those who appreciate the finer things in life.









# **Enhanced Aesthetic Appeal**

Refined textures inspired by natural stone elevate the visual allure of any garage space, infusing it with a touch of luxury and sophistication.




#### Finer Flake Texture

Elegant flakes finer than our classic offering, adding depth and sophistication to any garage space, elevating its timeless appeal and quality.



## FLOORTEX® STONE SERIES



#### SIX LUXURIOUS STONE-INSPIRED FLOORTEX® COLORS\* TO CHOOSE FROM










STEP 1 | DIAMOND GRIND SURFACE





# STEP 5 | CLEAR DURABLE FLOORTEX\* TOP COAT STEP 4 | DECORATIVE FLOORTEX\* FLAKES STEP 3 | PIGMENTED ADHESIVE BASE COAT STEP 2 | CRACK & CHIP REPAIR

